

## BOLA Schläuche, Bohlender BOLA Tubing

**Schläuche aus Fluorkunststoff (PTFE)**, nahezu universell chemisch resistent, temperaturbeständig von -200 bis +260°C.

| Innen-Ø ca.<br>mm | Außen-Ø ca.<br>mm | Mindestabnahme<br>m | Best.-Nr.   |
|-------------------|-------------------|---------------------|-------------|
| 0,5               | 1,0               | 10                  | 27 17 30004 |
| 0,8               | 1,6               | 10                  | 27 17 30005 |
| 1,0               | 1,6               | 10                  | 27 17 30032 |
| 1,0               | 2,0               | 10                  | 27 17 30006 |
| 1,2               | 1,8               | 10                  | 27 17 30033 |
| 1,5               | 3,0               | 10                  | 27 17 30036 |
| 1,6               | 3,2               | 10                  | 27 17 30009 |
| 2,0               | 3,0               | 10                  | 27 17 30011 |
| 2,0               | 4,0               | 10                  | 27 17 30012 |
| 3,0               | 5,0               | 3                   | 27 17 30014 |
| 4,0               | 6,0               | 3                   | 27 17 30016 |
| 4,35              | 6,35              | 3                   | 27 17 30041 |
| 6,0               | 8,0               | 3                   | 27 17 30020 |
| 8,0               | 10,0              | 1                   | 27 17 30023 |
| 10,0              | 12,0              | 1                   | 27 17 30026 |
| 12,0              | 14,0              | 1                   | 27 17 30027 |

ⓘ Bitte beachten Sie die Mindestabnahmemenge.

